



PRIMO S



Speed
52 kmph



Range
Upto 82 kmph*



Multiple
Battery Option



Charging time
3.5-4.5 Hrs*



Reverse
Gear



Turn by Turn
Navigation



USB
Charging Port



Call & SMS
Alert



Distance
to Empty

VEHICLE SPECIFICATIONS	
Specification	PRIMO S
Real Range	Upto 82 kmpc*
Speed	52 Kmph
Gradability	7 Degree+
Loading Capacity	150 kg
GVW (Gross Vehicle Weight)	255 kg
CHASSIS SPECIFICATIONS	
Chassis Specification	PRIMO S
Frame Type	Tubular Structure
Tyre Size Front	Rim: 10", Tyre: 90/90-10
Tyre Size Rear	Rim: 10", Tyre: 90/90-10
Tyre Type	Tubeless Tyre
Front Suspension	Telescopic
Rear Suspension	Hydraulic
Overall Dimension (LWH)	1800*720*1100
Ground Clearance	165 mm
Front Brake Type	Disc
Rear Brake Type	Drum
EV POWER TRAIN	
EV Power Train	PRIMO S
Motor Type	BLDC Hub
Motor Rated Power	1.07 Kw

BATTERY & CHARGING SPECIFICATIONS	
Battery & Charging	PRIMO S
Battery Type	Lithium-Ion LFP
Battery Capacity	2.04 Kwh
Battery Specification	64V 32Ah
No of Batteries	1
Battery (Fixed/ Detachable)	Detachable
Charger Amp	60V 10 Amp
Charging Time	3.5-4 Hrs
CLUSTER & CONNECTIVITY	
Cluster & Connectivity	PRIMO S
Cluster Type	Digital Segmented
Bluetooth Connectivity	Via Mobile App
Temperature, Time, Fault Finding Indicator,Battery % with Bar, Vehicle Speed Bar, Trip Meter, Odometer, Vehicle Gear/ Speed Mode,Expected Range	Yes
Navigation Turn Distance	Yes
Turn By Turn Navigation	Yes
Maintenance Symbol	Yes
Bluetooth Connectivity Symbol	Yes
Incoming Call Alert	Yes
Incoming SMS Alert	Yes

WARRANTY , AVAILABLE COLORS & PRICING

Warranty Type	PRIMO S
Vehicle Warranty	Standard Warranty 3 Years on Specific Components and 1 Year on Charger
Battery Warranty	2 + 1 Year* or 30,000 Km whichever is Earlier
Available Colors	Red-Black, Silver-Black, White-Black, Black-Silver, White, Black, Red, Silver
Ex Showroom	92,007/-

Manufactured By:- Jitendra New EV Tech. Pvt. Ltd.

B-88, Arihant Plaza, MIDC, Ambad, Nashik-422010 (MH)

Salesline-7057299999. www.jitendraev.com

Email : info@jitendraev.com Follow Us On:



**Chat on
WhatsApp**